



CAPACITY	DRIVE SHEAVE		BLOWER		BELT	C.D.		
	RPM	SHEAVE	BUSHING	RPM			SHEAVE	BUSHING
30 BHP	2450	2-5V11.7	SK-1 1/2	4500	2-5V6.2	SKX38MM	2-5VX800	25.8"

- NOTES:**
- #1. DIMENSIONS ARE IN INCHES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.
 - #2. STRUCTURAL SURFACES WILL BE CLEANED IN ACCORDANCE WITH SSPC-SP3 STANDARDS, FOLLOWED BY THE APPLICATION OF ONE COAT OF INDUSTRIAL PRIMER AND ONE COAT OF BLACK INDUSTRIAL ENAMEL.
 - #3. UNIT DLDV-45 TO BE INSTALLED ON THE SUPPORT WITH $\phi 1/2"$ -13UNC HEXAGONAL HEAD BOLTS.

WEIGHT: - LBS 980/445 KG.

PROJECT: -		SCALE: 1 = 1		DRAWING #:		REV.:	
TITLE: DL-DV-45 & SUPPORT / GENERAL ARRANGEMENT		DRAWN BY: B.V.		CHECKED BY: D.L.		DATE: 6.01.2012	
CUSTOMER: -		PROJECT #:		SHEET #:		GA_DLDV45&SUPPORT 1	
SURPRESSEUR 4S 108 BEAUVAS DELSON JB9 1W8 TEL: (450) 638-9563, FAX: (450) 638-9562		PROJECT #:		SHEET #:		DATE: 6.01.2012	